

## **Specification Sheet**

Part Number: 181-00203



**Product Description** 

Solid Wall Wiring Duct, 4" X 2", Non-Adhesive, PVC, White, 30ft/Box

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white,

gray and black, and is available in 6 foot lengths.

| Article Number      | 181-00203  |
|---------------------|--|
| Туре                | SD4X2  |
| Color               | White (WH)   |
| Features & Benefits | • A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. • Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. • Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately) |
| Quantity Per        | box  |

| Short Description                | Solid Wall Wiring Duct, 4" X 2", Non-Adhesive, PVC, White, 30ft/Box |
|----------------------------------|---|
| Global Part Name                 | SD4X2-PVC-WH  |
| Technical Description            | Non-Adhesive  |
|                                  |   |
| Length L (Imperial)              | 6.0   |
| Length L (Metric)                | 1.83  |
| Width W (Imperial)               | 4.0   |
| Width W (Metric)                 | 101.6   |
| Height H (Imperial)              | 2.07  |
| Height H (Metric)                | 52.6  |
| Mounting Hole Centers (Imperial) | 4.0   |
|                                  |   |
|                                  |   |
| Material                         | Polyvinylchloride (PVC)   |
| Material Shortcut                | PVC   |
| Flammability                     | Self-Extinguishing  |
| Halogen free                     | No  |
| Operating Temperature (Metric)   | +122°F (+50°C)  |

| Reach Complaint(Article 33)     | No   |
|---------------------------------|--|
| ROHS Complaint                  | Yes  |
| Certification/Specification WEB | CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A UL |
| UL Recognized (US)              | Yes  |
|                                 |  |
| Package Quantity(Imperial)      | 30   |
| Package Quantity (Metric)       | 9.14   |
| Customs Number                  | 3925900000                                       |

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $<sup>\</sup>hbox{@}$  2018 HellermannTyton. All rights reserved.