	CIFICATION CONTROL DRAWING		55A6500
itle	WIRE, RADIATION-CROSSLINKED, MODIFIED ETFE INSULATED, LIGHTWEIGHT, GENERAL PURPOSE, 600 VOLT	Date 10-18-05	Revision B
	This specification sheet forms a part of the latest issue of Raychem Specification	ecification 55A.	ł
COND	UCTOR – TIN-COATED COPPER NOTE: Controlled Free Tin-Coating Thickness – 40 micro inches (minimum)		
	ADDITIONAL REQUIREMENTS		
S	DLDERABILITY: 95% (minimum) coverage per MIL-STD-202, Method 208 (1 hour stear	n aging)	
	cept as specified above, this construction shall meet all the requirements of Raychem S AWG sizes 26 through 12.	Specification Sheet 5	5A0111
Tugo Elector in	Users should evaluate the suitability of this product for their application. Specifications are sub		
1/ COLORS AND C SUFFIXES MAY	Users should evaluate the suitability of this product for their application. Specifications are sult also reserves the right to make changes in materials or processing, which do not affect compliance OLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. OTHER CODES AND BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS TE PURCHASE ORDER.	with any specification, w	vithout notification to Buye Raychem Wire & Cable
1/ COLORS AND C SUFFIXES MAY	also reserves the right to make changes in materials or processing, which do not affect compliance OLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. OTHER CODES AND BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS	with any specification, w	vithout notification to Buye